mEmantracourt



Weighing Indicator / Controller for Fast Fill Operations



The ADW-FFW Weighing Indicator is to control high speed, high accuracy filling by weight for strain gauge or load cell applications. Either in a stand alone mode or in conjunction with a PLC

Introduction

Example operation:

On receipt of the start fill signal weightment is auto tared, and the relay contacts for fast and slow speed are closed, The system is optimised by a routine to ensure that, fast feed is held as long as possible.

In-flight compensation is applied to the slow feed and automatically adjusted to minimise final error.

When pre set values are reached, contacts turn off the fast and slow feeds. A 'weight complete' signal is given when within pre selected setting values and time, Auto tare will take place only when the value falls within a pre set auto tare band.

Specification at a Glance

- Fast 100 updates per second input
- Fast and slow fill feeds
- System speed optimisation
- Auto tare
- Auto calibration
- Auto 'in-flight' output
- 'Weight complete' output
- Comms 10 x fill selections switching
- Totaliser output



User Benefits

- All standard ADW15 systems features retained
- For fast fill and accurate fill control
- Stand alone or control with plc

Ideal Applications

- Silo & Weighing Industry
- Food Industry



mantracourt.com

ΠE

Related Product



ADW-BW Batch weighing controller, 12 components, 10 recipes



ADW-LW Weighing indicator, hopper discharge controller



ADW-SP16 Weighing controller with 16 set point relays

CE & Environmental

Storage temperature Operating temperature Relative humidity - 20 to +70°C - 10 to +50°C 95% maximum non condensing

CE Environmental Approvals European EMC Directive Low Voltage Directive

2004/108/EC 2006/95/EC



Issue 2.3 19-09-17

-17 mantra

mantracourt.com

sales@mantracourt.com tel