

m = mantracourt

Wireless Handheld Display for Running Line Tensiometer



Introduction

The T24-HLT has been designed specifically to operate with the T24-LT1 therefore enabling an OEM manufacturer to provide a complete running line tensiometer solution. The Handheld can cycle round the three measurement values of Load, Pay-out and Speed with the ability to tare the load and zero the pay-out values. Each measurement type has its own scaling, display resolution and ability to change the display name. A backlight is provided for low light operating conditions and a buzzer to warn of conditions such as overload and wireless communications failure.

Product Features

- Designed Specifically for Running Line Tensiometer
- Simple operation
- 800m (½ mile) range
- Audible warnings and feedback
- Long Battery life
- Tare / Zero / Gross function
- Sleep/ wake acquisition modules
- User controlled backlight
- Auto shut down
- Sealed to IP67 in a robust handheld enclosure



T24 System Overview



T24 Wireless Telemetry Sensor System is a modular wireless solution for industrial sensor applications.


High accuracy, high quality measurement is interfaced with simple yet powerful configuration and monitoring software.

Power Supply	
Power supply voltage	2.3 to 3.6 Vdc
2 off AA 1.5V primary cells	

Battery Life	
Based on Energizer L91 batteries	
Continuous operation	54 Hours
Standby mode (powered off)	> 5 Years

Radio	
Radio type	Licence exempt transceiver
Radio frequency	2.4 GHz
Transmit power	10 mW
Range	Up to 800 m

Environmental	
Operating temperature range	-10 to 50 °C
Storage temperature range (no batteries)	-40 to 85 ℃
Maximum humidity	95% non-
	condensing
IP rating	IP67/Nema4





T24-HLT

Running line tensiometer Handheld Telemetry Display

TR100-CA

Black leather case with clear viewing window with shoulder strap

Mantracourt Electronics Ltd

The Drive, Farringdon Exeter, Devon, UK EX5 2JB

Tel: +44 (0)1395 232020 Email: sales@mantracourt.com

mantracourt.com













ME

T24 Product Sheet Issue 2.0 08-09-15 tel +44 (0)1395 232020 mantracourt.com sales@mantracourt.com